

Holdfire Carefree Standard is a dual purpose unit that offers selectable hold-open or swing free functions.

- Low cost, simple mechanism
- Selectable hold open or swing free function
- Ideal for corridor, communal and staff area doors
- Safe, slow swing speed in fire condition
- A comprehensive 10 year guarantee
- Suitable for both new construction and retrofit
- Fully tested to British and European standards
- Available in a wide range of finishes and colours

Why Carefree Standard?

Carefree Standard is a dual purpose unit that offers selectable hold-open or swing free functions.

In hold-open mode it offers a facility to firmly hold doors open so that residents cannot easily close the door. This system is ideal for corridor doors or some communal rooms where some residents may maliciously close the door to exclude others.

Many conventional hold-open systems need a button to be pressed to release the door manually, (which most staff never do resulting in damage to the doors and devices). A particular feature of Carefree Standard is that the door is specifically designed to be manually released with a simple, firm pull making operation intuitive for staff and preventing damage to the doors and fittings.

Swing Free:

Carefree Standard also offers a swing free facility but without the additional safety features of Carefree Plus. The swing free function is simply selected by changing a screw position on the unit. Swing free mode without the safety features is ideally suited to staff areas such as offices, nurse stations, kitchens and laundry rooms.

Additionally, Carefree Standard in swing free mode has been used very successfully for Flat entrance doors in sheltered housing schemes. The requirement here is for the door to be easily opened but as Flat doors are generally closed the anti-slam and anti-drift feature of Carefree Plus are less relevant.



Other Carefree products from Holdfire:

Carefree Door Closer:

A DDA compliant simple door closer

Carefree Duo:

A unique system for doors where a closing action is required for privacy reasons but a conventional fire door closer is too heavy

Carefree Plus:

Swing free closer with anti-slam and anti-drift features for care facilities

CAREFREE STANDARD

One of the most versatile units
on the market, offering:

- Slimline profile allows closer to be positioned behind most doors
- Parallel arm or projecting arm configurations
- Push or pull side installation & either handed
- Will not warp doors like traditional door holders
- Latch and closing speed control
- Hold open from 70 to 170 degrees
- Selectable power (template) up to size 4

Design:

Traditionally door closers with built in hold-open or swing free mechanisms have been expensive, ugly, complex looking pieces of equipment. In keeping with the Holdfire design philosophy, the Holdfire unit is a slimline, low profile mechanism that is even smaller than many types of basic overhead closer.

Yet despite its size, this versatile system offers the capability to allow the door to swing-free or securely hold the door at any angle from 70-170 degrees, making it suitable for both bedroom and corridor doors.

With a powerful closing engine and two speed adjustments, Carefree can be configured to slowly close when the fire alarms are activated and powerfully drive the door past the cold smoke seals to latch.

We are the only company that gives a full 10 year guarantee on both mechanical and electrical aspects, including the wire loop from the unit to the door frame.

For further information, please call:

0800 111 6104

Alternatively, you can email us at:

info@holdfire.com


Or, visit the website:

www.holdfire.com


HOLDFIRE
SELF CLOSING DOOR SOLUTIONS

Technical Data:

Parallel Arm configuration



Projecting Arm configuration



Finishes:

- Spray silver
- Brushed stainless steel
- Brass plated
- Chrome plated
- Colour matching

Power requirement:

24V DC, 2.8W

Standards:

BS EN 1155 which incorporates BS EN 1634.
Can be installed to meet BS 7273 Cat A.